

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F.
Larsen

January 1936

Test 259: Cletrac BG

Tractor Museum

University of Nebraska-Lincoln, TractorMuseumArchives@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>

 Part of the [Applied Mechanics Commons](#)

Museum, Tractor, "Test 259: Cletrac BG" (1936). *Nebraska Tractor Tests*. 862.

<https://digitalcommons.unl.edu/tractormuseumlit/862>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 259

Dates of test: June 16 to July 10, 1936.
Name and model of tractor: CLETRAC BG
Manufacturer: Cleveland Tractor Company, Cleveland, Ohio.
Manufacturer's rating: NOT RATED.

B R A K E H O R S E P O W E R T E S T S

H. P.	:Crank : :shaft :	Fuel Consumption :Gals. : H. P. :Lbs. per:	Water Consumption : per hour gallons :	Temp. : Deg. F. :	:Barometer :Inches of :Mercury
:speed :	:R.P.M. :	: per : hour :	: Cool- : In : : ing : fuel : Total :	:Cool- : : ing : Air : :med. : :	

TEST B 100% MAXIMUM LOAD. TWO HOURS

39.07 : 1401 : 4.635 : 8.43 : 0.728 : 0.000 : 0.000 : 0.000 : 192 : 80 : 29.080

TEST C OPERATING MAXIMUM LOAD. ONE HOUR

38.42 : 1398 : 4.363 : 8.81 : 0.697 : 0.000 : 0.000 : 0.000 : 197 : 82 : 29.010

TEST D RATED LOAD. ONE HOUR

35.03 : 1401 : 4.096 : 8.55 : 0.718 : 0.000 : 0.000 : 0.000 : 193 : 82 : 29.005

TEST E *VARYING LOAD. TWO HOURS

34.99	: 1405	: 4.207	: 8.32	: 0.738	: --	: --	: --	: 192	: 82	: --
1.34	: 1625	: 2.072	: 0.65	: 9.493	: --	: --	: --	: 154	: 83	: --
19.28	: 1537	: 3.308	: 5.83	: 1.053	: --	: --	: --	: 171	: 84	: --
36.68	: 1323	: 4.085	: 8.98	: 0.684	: --	: --	: --	: 198	: 84	: --
9.81	: 1584	: 2.697	: 3.64	: 1.688	: --	: --	: --	: 167	: 87	: --
26.87	: 1443	: 3.655	: 7.35	: 0.835	: --	: --	: --	: 185	: 87	: --
21.50	: 1486	: 3.337	: 6.44	: 0.953	: 0.000	: 0.000	: 0.000	: 178	: 84	: 29.005

*20 minute runs. Last line is average for two hours.

D R A W B A R H O R S E P O W E R T E S T S

H. P.	: Draw : : bar :	Speed : miles :	Crank : : shaft :	Slip : : on :	Fuel Consumption : H. P. : Lbs. :	Water: : used :	Temp. : :	:Barometer :Inches of :Mercury
: pull : : pounds :	: per : hour :	: speed : : R.P.M. :	: drive: : wheels :	: Gal. : : per : : hour :	: per : H.P. :	: Gal. : : per : hour :	:Cool- : : ing : :med. : :	

TEST F 100% MAXIMUM LOAD. Second GEAR.

28.27 : 4088 : 2.59 : 1399 : 2.46:-----Not Recorded-----: 212 : 99: 28.725

TEST G OPERATING MAXIMUM LOAD

27.20	: 6131	: 1.66	: 1399	: 8.54:-----Not Recorded-----	: 194	: 95: 28.680
27.53	: 3972	: 2.60	: 1400	: 2.27:-----"-----	: 210	: 98: 28.705
26.32	: 2882	: 3.43	: 1398	: 1.50:-----"-----	: 205	: 94: 28.450

TEST H RATED LOAD, TEN HOURS. Second GEAR.

23.03 : 3309 : 2.61 : 1400 : 1.85:3.755: 6.13 :1.001 :0.132: 203 : 94: 28.770

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
 AGRICULTURAL COLLEGE, LINCOLN

Copy of Report of Official Tractor Test No. 259

BRIEF SPECIFICATIONS

MOTOR: Make Hercules Serial No. 563217 Type 6 cylinder, vertical
 Head L Mounting Crankshaft lengthwise
 Bore and stroke: 3 3/4" x 4 1/4" Rated R. P. M. 1400
 Port Diam. Valves: Inlet 1 1/2" Exhaust 1 3/8"
 Belt pulley: Diam. 12" Face 8 1/2" R. P. M. 1050
 Distributor: Delco-Remy Model 645 H
 Carburetor Tillotson Model Y-8-C Size 1 1/4"
 Governor Hercules No. -- Type Centrifugal
 Air Cleaner Vortex Type Oil-washed, wire-filter
 Lubrication Pressure

CHASSIS: Type Tracklayer Serial No. 4C36 Drive Enclosed gear
 Clutch Long Type Two-plate, dry Operated by Foot pedal
 Advertised speeds, miles per hour: First 1.8 Second 2.625
 Third 3.5 Reverse 1.375
 Measured length of track 16.7031 feet Face 14"
 Lugs: Type Removable rolled steel cleats No. per track 30
 Size 14" long x 1 7/8" high
 Seat Upholstered
 Total weight as tested (with operator) 8686 pounds.

FUEL AND OIL:

Fuel Gasoline (68-70 Octane) Weight per gallon 6.14 pounds.
 Oil S.A.E. Viscosity No. 30
 Total oil to motor 2.671 gallons
 Total drained from motor 0.977 gallons
 Total time motor was operated 65 hours

The oil was drained
 once - at the end of
 the test.

UNIVERSITY OF NEBRASKA - AGRICULTURAL ENGINEERING DEPARTMENT
AGRICULTURAL COLLEGE, LINCOLNCopy of Report of Official Tractor Test No. 259REPAIRS AND ADJUSTMENTS

During the rated load drawbar test, the action of the external parts of the governor mechanism became sluggish. To restore proper action, the dust was washed from the parts and the cam of the cam-and-follower group was polished.

REMARKS

All results shown on page 1 of this report were determined from observed data and without allowances, additions or deductions. Tests B and F were made with carburetor set for 100% maximum horsepower and these figures were used in determining the ratings recommended by the A.S.A.E. and S.A.E. tractor rating codes. Tests C, D, E, G and H were made with an operating setting of the carburetor (selected by the manufacturer) of 98.3% of maximum horsepower.

Observed maximum horsepower (tests B & F) Drawbar 28.27 Belt 39.07

Sea level (calculated) maximum horsepower Drawbar 30.53 Belt 40.95
(Based on 60° F. and 29.92" Hg.)

Highest permissible horsepower ratings Drawbar 22.90 Belt 34.81
(As recommended by A.S.A.E. and S.A.E.
codes)

We, the undersigned, certify that the above is a true and correct report of official tractor test No. 259.

Carlton L. Zink
Engineer-in-charge

E. E. Brackett

C. W. Smith

L. E. Hurlbut